

# Material Safety Data Sheet

U.S. Department of Labor



May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

IDENTITY (As Used on Label and List)  
Sargent Gothic Molded Crayon

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

## Section I

Manufacturer's Name: Sargent Art Inc  
Address (Number, Street, City, State, and ZIP)  
100 E Diamond Ave.  
Hazleton, PA  
18201

Emergency Telephone Number: (570) 454-3596  
Telephone Number for Information: (570) 454-3596

Date Prepared: 10/22/99  
Signature of Preparer (optional)

## Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
---	----------	-----------	--------------------------	-------------

All CP/AP products are certified by a nationally recognized authority on toxicology associated with a leading university to contain no known toxic materials in sufficient quantities to be injurious to the human body even if ingested.

Conforms to ASTM D4236

## Section III - Physical/Chemical Characteristics

Boiling Point	550° - 750°F	Specific Gravity (H <sub>2</sub> O = 1)	.8 - 1.1
Vapor Pressure (mm Hg.)	n/a	Melting Point	125° - 145°F
Vapor Density (AIR = 1)	n/a	Evaporation Rate (Butyl Acetate = 1)	less than .01
Solubility in Water	Negligible		
Appearance and Odor	64 Various colors, slight wax color		

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	Flammable Limits	LEL	UEL
n/a	n/a	n/a	n/a
Extinguishing Media			
Carbon Dioxide, Foam, Sand			
Special Fire Fighting Procedures			
none			
Unusual Fire and Explosion Hazards			
Do not store with strong oxidizers			

## Section V - Reactivity Data

Stability	Unstable Stable	X	Conditions to Avoid
Incompatibility (Materials to Avoid)			
Solvents will dissolve product			
Hazardous Decomposition or Byproducts			
Carbon Monoxide			
Hazardous Polymerization	May Occur		Conditions to Avoid
(Reproduce locally)	Will Not Occur	X	Contact with strong oxidizers. Over heating or burning may release highly irritating fumes.

OSHA 174, Sept. 1985

## Section VI - Health Hazard Data

Route(s) of Entry:                      Inhalation? no                      Skin? no                      Ingestion? Possible (See Below)

Health Hazards (Acute and Chronic)  
This product is certified in a program of toxicological evaluation by a medical expert to contain no materials in sufficient quantity to be toxic or injurious to humans or cause acute or chronic health problems

Carcinogenicity:                      NTP? n/a                      IARC Monographs? n/a                      OSHA Regulated? no

Signs and Symptoms of Exposure: n/a  
Medical Conditions Generally Aggravated by Exposure: n/a  
Emergency and First Aid Procedures: If ingested call a physician immediately

## Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled:  
Recover free product. Conform to State and Local regulations.

Waste Disposal Method:  
In accordance with local regulations

Precautions to Be taken in Handling and Storing:  
Store at room temperature.

Other Precautions:  
do not use around open flame.

## Section VIII - Control Measures

Respiratory Protection (Specify Type):  
none

Ventilation	Local Exhaust: none	Special: none
	Mechanical (General): none	Other: none

Protective Gloves: none                      Eye Protection: none

Other Protective Clothing or Equipment  
none

Work/Hygienic Practices  
Cleans, safe normal practices

\* U.S.G.P.O.: 1986 - 491 - 529/45775